

Product data sheet

Specifications



Symmetra PX250/500kW Battery Enclosure Sidecar for Remote Battery Solution with 1000A Fuse Kit

SYBSC500K500

Overview

Lead time Usually Ships within 6 Weeks

Main

Main Input Voltage 480 V 3 phase
400 V 3 phase

Battery Type VRLA

Provided Equipment User Manual

Batteries & Runtime

Device mounting Enclosed battery cabinet

Battery Volt-Amp-Hour Capacity 0 VAh

Physical

Color Black

Height 78.4 in (199.1 cm)

Width 11.8 in (30 cm)

Depth 42.1 in (107 cm)

Net Weight 327.70 lb(US) (148.64 kg)

Conformance

Product Certifications cUL Listed
CE
UL Listed
VDE

Environmental

Ambient Air Temperature for Operation 32.0000000000...104.0000000000 °F (0...40 °C)

Operating altitude 0...3333 ft

Relative Humidity 0...95 %

Ambient Air Temperature for Storage 5.0000000000...104.0000000000 °F (-15...40 °C)

Storage altitude 0...50000 ft (0.0000000000...15240.0000000000 m)

Storage Relative Humidity 0...95 %

Ordering and shipping details

GTIN 731304253587

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	84.6 in (215 cm)
Package 1 Width	47.6 in (121 cm)
Package 1 Length	29.3 in (74.5 cm)
Package 1 Weight	411.87 lb(US) (186.82 kg)

Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)

Eu Rohs Directive

Pro-active compliance (Product out of EU RoHS legal scope)

[EU RoHS Declaration](#)
