

Product data sheet

Specifications



High Performance Long Life 10 Yrs Battery Module for Symmetra PX 48/96/160KW

SYBT9-B4LL

Overview

Lead time Usually in Stock

Main

Battery Type VRLA
Provided Equipment Installation guide

Batteries & Runtime

Battery Placement Internal Battery
Battery blocks per string 4
Battery Voltage 384 V
Battery Volt-Amp-Hour Capacity 3456 VAh

Physical

Height 6.3 in (15.9 cm)
Width 16.9 in (42.8 cm)
Depth 27.6 in (70 cm)
Net Weight 221.45 lb(US) (100.45 kg)

Conformance

Standards UL 1778
Product Certifications CE
Eurobat General Purpose

Environmental

Ambient Air Temperature for Operation 64.4...80.6 °F (18...27 °C)
Operating altitude 0...3333 ft
Relative Humidity 0...95 %
Ambient Air Temperature for Storage 5.000000000...104.000000000 °F (-15...40 °C)
Storage altitude 0...50000 ft (0.000000000...15240.000000000 m)
Storage Relative Humidity 0...95 %

Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1	1
Package 1 Height	7.09 in (18 cm)
Package 1 Width	31.9 in (81 cm)
Package 1 Length	23.6 in (60 cm)
Package 1 Weight	236.8 lb(US) (107.4 kg)

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)



Take-back Transparency RoHS/REACH

Resource performance

 Take-Back Program Available

Certifications & Standards

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Pro-active compliance (Product out of EU RoHS legal scope)

[EU RoHS Declaration](#)

Environmental Disclosure

[Product Environmental Profile](#)