

Product data sheet

Specifications



Symmetra PX250/500 Third Party Switch Gear Kit

SYOPT007

Overview

Presentation Ancillary Monitor Board, EPO Connection and Trip Board, and 50 meter connection cables for installing either the custom switchgear used in parallel Symmetra PX 250/500kW systems or a third-party maintenance bypass panel used with the Symmetra PX 250/500kW without MBwD UPS.

Lead time Usually Ships within 3 Weeks

Main

Provided Equipment User Manual

Physical

Height 1.7 in (4.3 cm)

Width 3.7 in (9.3 cm)

Depth 1.4 in (3.5 cm)

Net Weight 0.99 lb(US) (0.45 kg)

Conformance

Product Certifications CE
UL Recognized

Environmental

Ambient Air Temperature for Operation 32.0000000000...104.0000000000 °F (0...40 °C)

Operating altitude 0...15000 ft

Relative Humidity 0...95 %

Ambient Air Temperature for Storage 32.0000000000...104.0000000000 °F (0...40 °C)

Storage altitude 0...50000 ft (0.0000000000...15240.0000000000 m)

Storage Relative Humidity 0...95 %

Ordering and shipping details

GTIN 731304278764

Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1 1

Package 1 Height 7.8 in (19.7 cm)

Package 1 Width 3.1 in (8 cm)

Package 1 Length	3.7 in (9.5 cm)
-------------------------	-----------------

Package 1 Weight	2.006 lb(US) (0.91 kg)
-------------------------	------------------------

Contractual warranty

Warranty	1 year repair or replace
-----------------	--------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)

Eu Rohs Directive

Compliant

[EU RoHS Declaration](#)
