

# Product data sheet

Specifications



## APC Back-UPS 1350, Compact Tower, 1350VA, 120V, AVR, LCD, 10 NEMA outlets (5 surge)

BX1350M

### Overview

Lead time Usually in Stock

### Main

Main Input Voltage	120 V
Main Output Voltage	120 V
Kw Rating	810 W
Rated power in VA	1350 VA
Product or Component Type	Uninterruptible power supply (UPS)
Input Connection Type	NEMA
output connection type	5 NEMA 5-15R 5 NEMA 5-15R surge
Cable length	6 ft (1.8 m)
Number of cables	1
Battery Type	Lead-Acid battery

### Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a>
Efficiency	<a href="#">View Efficiency Graph</a>
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	16 h
RBC Quantity	1
Battery Charge Power (Watts)	9 W rated
Extendable Run Time	0
Replacement battery	<a href="#">APCRBC123</a>

### General

Provided equipment	User Manual USB cable
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

## Physical

Height	9.8 in (25 cm)
Width	3.9 in (10 cm)
Depth	15.04 in (38.2 cm)
Net Weight	22.5 lb(US) (10.2 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable
Two post mountable	0
USB compatible	No

## Input

Input Frequency	60 Hz +/- 3 Hz
Efficiency at full load	88...139 V
Maximum Input Current per Phase	12 A
Switching current capacity	15 A

## Output

Max Configurable Power (Watts)	810 W
Output Frequency (sync to mains)	60 Hz sync to mains
Topology	Line Interactive
Waveform Type	Stepped approximation to a sinewave
Maximum configurable power in VA	1350 VA
Transfer Time	8ms typical : 10 ms maximum

## Conformance

Product Certifications	California (CEC) Battery Charger ENERGY STAR V2.0 (USA) TUV C-US certified
Equipment protection policy	Lifetime : \$250000

## Environmental

Ambient Air Temperature for Operation	32.0000000000...104.0000000000 °F (0...40 °C)
Relative Humidity	0...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5.0000000000...113.0000000000 °F (-15...45 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 ft (0.0000000000...15240.0000000000 m)
Acoustic level	45 dBA
Online Thermal Dissipation	67.6 Btu/h

## Communications & Management

Control panel	Multi-function LCD status and control console
---------------	---

---

<b>Alarm</b>	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
--------------	--

## Surge Protection and Filtering

---

<b>Surge energy rating</b>	789 J
----------------------------	-------

---

<b>Filtering</b>	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : mee
------------------	--

---

<b>Data line protection</b>	Coaxial cable for CATV/SATV/modem/audio-video
-----------------------------	---

## Ordering and shipping details

---

<b>GTIN</b>	731304331773
-------------	--------------

## Packing Units

---

<b>Unit Type of Package 1</b>	PCE
-------------------------------	-----

---

<b>Number of Units in Package 1</b>	1
-------------------------------------	---

---

<b>Package 1 Height</b>	13.7 in (34.8 cm)
-------------------------	-------------------

---

<b>Package 1 Width</b>	19.3 in (49.1 cm)
------------------------	-------------------

---

<b>Package 1 Length</b>	8.9 in (22.7 cm)
-------------------------	------------------

---

<b>Package 1 Weight</b>	26.2 lb(US) (11.9 kg)
-------------------------	-----------------------

---

<b>SCC14</b>	10731304331770
--------------	----------------

## Contractual warranty

---

<b>Warranty</b>	3 years repair or replace
-----------------	---------------------------

## Sustainability


**Green Premium™** label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

[Learn more about Green Premium >](#)



Energy Efficient Take-back Transparency RoHS/REACH

## Resource performance


 Energy Efficient Product

---


 Take-Back Program Available

---

## Well-being performance

 Mercury Free

---

 Rohs Exemption Information Yes

---

## Environmental Certifications

 Energy Star® ENERGY STAR UPS V2.0 (USA)

---

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

---

Eu Rohs Directive Compliant with Exemptions

---

Environmental Disclosure [Product Environmental Profile](#)

---

Circularity Profile [End of Life Information](#)

---

**California Proposition 65** WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

---