

Product data sheet

Specifications



APC Back-UPS Pro, 1350VA/
810W, Tower, 120V, 10x NEMA
5-15R outlets, Sine Wave, AVR,
USB Type A + C ports, LCD, User
Replaceable Battery

BR1350MS

Overview

Lead time Usually in Stock

Main

Main Input Voltage	120 V
Main Output Voltage	120 V
Kw Rating	810 W
Rated power in VA	1350 VA
Product or Component Type	Uninterruptible power supply (UPS)
Input Connection Type	NEMA
output connection type	6 NEMA 5-15R 4 NEMA 5-15R surge
Cable length	6 ft (1.8 m)
Number of cables	1
Battery Type	Lead-Acid battery

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Included Battery Modules	1
Battery Slots Empty	0
Typical recharge time	16 h
RBC Quantity	2
Battery Charge Power (Watts)	10 W rated
Battery life	3...5 year(s)
Replacement battery	APCRBC161
Extendable Run Time	0

General

Provided equipment	Coaxial cable User Manual USB cable
product web sub-family	Gaming performance

Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Height	10.2 in (26 cm)
Width	3.9 in (10 cm)
Depth	14.5 in (36.8 cm)
Net Weight	25.8 lb(US) (11.7 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

Input Frequency	60 Hz +/- 3 Hz
Efficiency at full load	88...147 V
Maximum Input Current per Phase	12 A
Switching current capacity	15 A

Output

Max Configurable Power (Watts)	810 W
Output Frequency (sync to mains)	60 Hz +/- 3 Hz sync to mains
Topology	Line Interactive
Waveform Type	Sine wave
Maximum configurable power in VA	1350 VA
Transfer Time	8ms typical : 10 ms maximum

Conformance

Product Certifications	ENERGY STAR V2.0 (USA) NOM TUV C-US certified
Equipment protection policy	Lifetime : \$500000

Environmental

Ambient Air Temperature for Operation	32.0000000000...104.0000000000 °F (0...40 °C)
Relative Humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5.0000000000...104.0000000000 °F (-15...40 °C)
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0...10000 ft (0.0000000000...3048.0000000000 m)
Acoustic level	45 dBA

Communications & Management

Control panel Multi-function LCD status and control console

Surge Protection and Filtering

Surge energy rating 1080 J

Filtering Full time multi-pole noise filtering :5% of IEEE surge let-through : zero clamping response time: in

Ordering and shipping details

Category 11309-APC RESALE PRODUCTS

Discount Schedule APC1

GTIN 00731304335399

Returnability No

Country of origin PH

Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1 1

Package 1 Height 14.12 in (35.87 cm)

Package 1 Width 19.0 in (48.2 cm)

Package 1 Length 8.8 in (22.3 cm)

Package 1 Weight 29.3 lb(US) (13.3 kg)

SCC14 10731304335396

Contractual warranty

Warranty 3 years repair or replace

Sustainability


Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)




Energy Efficient Take-back Transparency RoHS/REACH


Resource performance

 Energy Efficient Product

 Take-Back Program Available

Well-being performance

 Mercury Free

 Rohs Exemption Information [Yes](#)

Environmental Certifications

 Energy Star® [ENERGY STAR UPS V2.0 \(USA\)](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive [Compliant with Exemptions](#)

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)

California Proposition 65 [WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to \[www.P65Warnings.ca.gov\]\(http://www.P65Warnings.ca.gov\)](#)
