

APC 144kVA Modular Power Distribution Unit, Isolation Transformer, 600:208V, 72 Poles, 2 Subfeed

PDPM150L6F

Overview

Presentation	A fully scalable power distribution system that cost-effectively provides high levels of availability and enables the quick addition of circuits and cord-sets.
Lead time	Usually Ships within 6 Weeks

Main

Main Input Voltage	600 V 3 phase
Main Output Voltage	208 V 3 phase
Provided Equipment	Installation guide

Physical

Color	Black
Height	79.02 in (200.7 cm)
Width	23.6 in (60 cm)
Depth	42.09 in (106.9 cm)
Net Weight	1942.3 lb(US) (881 kg)
Mounting Location	Front
Mounting preference	No preference
Mounting Mode	Not rack-mountable

Input

Input Frequency	60 Hz
Max line current	141 A
Load Capacity	144000 VA

Output

Protection Type Circuit breaker

Conformance

Standards	UL 60950-1
Product Certifications	cUL Listed CSA

Environmental

Ambient Air Temperature for Operation	23.0000000000104.0000000000 °F (-540 °C)
Relative Humidity	095 %
Operating altitude	09842 ft
Ambient Air Temperature for Storage	-13.0000000000149.0000000000 °F (-2565 °C)
Storage Relative Humidity	095 %
Storage altitude	050000 ft (0.000000000015240.0000000000 m)

Ordering and shipping details

GTIN 731304295402

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	84.8 in (215.3 cm)
Package 1 Width	48.0 in (121.9 cm)
Package 1 Length	40.000000000 in (101.6 cm)
Package 1 Weight	2043.7 lb(US) (927 kg)

Contractual warranty

Warranty 1 year repair or replace

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Learn more about Green Premium >

Eu Rohs Directive

Jul 26, 2024

Under investigation