

# Product data sheet

Specifications



## APC 150kVA Modular PDU Bottom Feed Side Car, 300mm

PDPM150SC

### Overview

**Lead time** Usually Ships within 3 Weeks

### Main

**Main Input Voltage** 208 V  
208 V 3 phase  
480 V 3 phase  
600 V 3 phase

**Main Output Voltage** 208 V  
208 V 3 phase  
415 V 3 phase  
480 V 3 phase  
600 V 3 phase

**Provided Equipment** Installation guide

### Physical

**Color** Black

**Height** 78.9 in (200.4 cm)

**Width** 11.8 in (30 cm)

**Depth** 42.1 in (107 cm)

**Net Weight** 295.4 lb(US) (134 kg)

**Mounting preference** No preference

**Mounting Mode** Not rack-mountable

### Input

**Input Frequency** 60 Hz

**Number of input connectors** 1 Hard Wire 5-wire (3PH + N + G)

**Input current limits** 200 A

### Output

**Maximum Total Current Draw per Phase** 200 A

### Conformance

**Standards** UL 60950-1

### Environmental

**Ambient Air Temperature for Operation** 23.0000000000...104.0000000000 °F (-5...40 °C)

Relative Humidity	0...95 %
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	-13.0000000000...149.0000000000 °F (-25...65 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...10000 ft (0.0000000000...3048.0000000000 m)

## Ordering and shipping details

GTIN	731304296256
------	--------------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	84.6 in (215 cm)
Package 1 Width	47.6 in (121 cm)
Package 1 Length	33.4 in (84.8 cm)
Package 1 Weight	341.7 lb(US) (155 kg)
SCC14	10731304296253

## Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

[Learn more about Green Premium >](#)

Eu Rohs Directive

Under investigation

---