

Product data sheet

Specifications



APC Modular Power Distribution Unit, 266kVA, 400A, 480V:415V Auto-transformer, 72 Pole, 300mm

PDPM288G6H

Overview

Lead time Usually Ships within 6 Weeks

Main

Main Input Voltage 480 V 3 phase

Main Output Voltage 230 V
240 V

Other Output Voltage 240 V

Provided Equipment Installation guide
User Manual

Physical

Height 78.4 in (199.1 cm)

Width 11.7 in (29.8 cm)

Depth 42.2 in (107.2 cm)

Net Weight 1152.42 lb(US) (522.73 kg)

Mounting Location Front

Mounting preference No preference

Mounting Mode Not rack-mountable

Input

Input Frequency 60 Hz

Max line current 320 A

Load Capacity 266 kVA

Output

Maximum Total Current Draw per Phase 370 A

Conformance

Product Certifications UL Listed

Ordering and shipping details

GTIN 731304266273

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	84.02 in (213.4 cm)
Package 1 Width	42.2 in (107.2 cm)
Package 1 Length	11.7 in (29.8 cm)
Package 1 Weight	1202.51 lb(US) (545.45 kg)

Contractual warranty

Warranty	1 year repair or replace
-----------------	--------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)



Transparency RoHS/REACH

Well-being performance

Mercury Free

Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Pro-active compliance (Product out of EU RoHS legal scope)

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information.

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)