



APC Modular Remote Power Panel, 144kVA, 400A, 208V, 72 Pole, 300mm

PDPM144F

Overview

Presentation	A fully scalable power distribution system that cost-effectively provides high levels of availability and enables the quick addition of circuits and cord-sets.
Lead time	Usually Ships within 3 Weeks

Main

Main Input Voltage	208 V 3 phase
Main Output Voltage	208 V 3 phase
Provided Equipment	Installation guide

Physical

_	
Height	78.8 in (200.2 cm)
Width	11.8 in (30 cm)
Depth	42.4 in (107.7 cm)
Net Weight	352.7 lb(US) (160 kg)
Mounting Location	Front
Mounting preference	No preference
Mounting Mode	Not rack-mountable

Input

Input Frequency	60 Hz
Acceptable Input Voltage	200240 V
Max line current	400 A
Load Capacity	144 kW

Output

Maximum Total Current Draw per 400 /

Phase

Conformance

Standards	OSHPD	
Product Certifications	UL Listed	

Ordering and shipping details

GTIN 731304271611

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	88.5 in (224.8 cm)
Package 1 Width	47.5 in (120.6 cm)
Package 1 Length	33.5 in (85.1 cm)
Package 1 Weight	401.84 lb(US) (182.27 kg)

Contractual warranty

Warranty 1 year repair or replace



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Learn more about Green Premium >





Transparency RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information